

PRODUCT BROCHURE

CAMELBACK TREAD RUBBER



APPLICATION

TRUCK

TRACTOR (Front & Rear)

OFF THE ROAD (OTR)

	CAMEL BACK TREAD RUBBER (CBTR) - TRUCK												
SL. NO.	SIZE	Base Width (mm)	Crown Width (mm)	Tread Thickness (mm)	Wing Thickness (mm)	Wing Width (mm)	Roll Length (Feet's)		R	oll Weight (kgs)			Application / Tyre Size
	Tolerance	+2 mm	+2 mm	+0.5 mm	+0.3 mm	+2 mm	+3"	Pre	Premium		Regular		Tyre Size
1	74 - 22	188	-	17.5	-	-	31'-9"	36.5	- 37.0	37.5 - 38.0)	10.00-X-20
2	78 - 22	198	-	17.5	-	-	31'-9"	38.0	- 38.5	39.0 - 39.5		5	10.00-X-20
3	78 - 24	198	-	17.5	•		31'-9"	40.0	- 40.5		41.0 - 41.5	5	10.00-X-20
4	80 - 22	206	-	18.6	-	-	31'-9"	42.5	42.5 - 43.0		43.5 - 44.0		10.00-X-20
5	84 - 22	215	-	17.5	-	-	32'-3"	43.8	- 44.3		44.5 - 45.0		10.00-X-20
6	74-100-20	254	188	15.9	9.00	33	31'-9"	40.0	40.0 - 40.5		41.0 - 41.50		10.00-X-20
7	74-110-20	280	188	15.9	9.00	46	31'-9"	42.4	- 43.0	43.4 - 44.0		10.00-X-20	
		CAN	JEL I	BACK	TRE	AD RL	JBBEI	3 (C	BTR)	- TRACTOR			
		Base	Crown	Middle	Middle	Total	Wing	Wing	Roll	No of	s in Roll Weight		
SL.	SIZE	Width	Width	Width	Thickness	100.10-0.00.00.00.00		Width	Booking	Rolls in			Application /
NO.		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	Length	the	Premium	Regular	Tyre Size
	Tolerance	+3 mm	+3 mm	+3 mm	+0.5 mm	+0.5 mm	+0.5 mm	+2 mm	(Feet's) +2.0"	Packag Nos	-0/+1	l O Ka	-
1	50-70-16	178	127	-		12.70	5.60	25	21'-9"	2	14.85	15.10	600-X-16
2	50-70-18	178	127	-	-	14.30	5.60	25	21'-9"	2	16.55	16.85	600-X-16
3	50-74-16	188	127	-	-	12.70	5.60	30	21'-9"	2	15.50	15.80	600-X-16
4	50-74-18	188	127		-	14.30	5.60	30	21'-9"	2	16.80	17.10	600-X-16
5	100-150-24	381	254		-	19.10	6.70	63	12 1/2	1	25.20	25.60	12.4-X-28
6	100-150-26	381	254	-	-	20.60	6.70	63	12 ½	1	27.00	27.40	12.4-X-28
7	100-150-28	381	254	-	-	22.20	6.70	63	12 1/2	1	28.80	29.30	12.4-X-28
8	100-150-28-XL	381	254	-	-	22.20	6.70	63	21 1/2	1	50.40	51.20	12.4-X-28
9	110-150-24	381	279	-	-	19.10	6.70	50	12 ½	1	26.26	27.10	13.6-X-28
10	110-150-26	381	279	-	-	20.60	6.70	50	12 ½	1	28.50	29.00	13.6-X-28
11	110-150-26-XL	381	279		-	20.60	6.70	50	21'-9"	1	50.70	51.70	13.6-X-28
12	110-150-28	381	279	-	•	22.20	6.70	50	12 1/2	2	30.50	31.00	13.6-X-28
13	110-150-28-G	381	279	-	-	22.60	11.60	50	16'-2"	1	43.60	44.40	13.6-X-28
14	110-150-28-XL	381	279	-	-	22.20	6.70	50	20'-6"	1	50.70	51.70	13.6-X-28
15	110-150-30	381	279	-	-	23.80	10.00	50	12 ½	2	33.50	34.30	13.6-X-28
16	45-110-150-30	381	279	114	28.80	23.80	6.70	50	17.0	1	49.80	50.50	13.6-X-28
17	110-150-32	381	279	-	-	26.20	7.50	50	12 1/2	1	34.50	35.00	13.6-X-28
18	110-160-30-XL	406	279	-	-	23.80	6.70	63	18'-9"	1	50.50	51.50	13.6-X-28
19	120-160-30	406	305	-	-	24.20	8.20	50	14.0	1	40.70	41.40	14.9-X-28
											40.00		13.00-X-24
20	120-180-34	457	305	-	-	27.80	9.80	75	13'-8"	1	48.20	48.80	14.00-X-24 14.00-X-24
21	125-175-28	445	318	-	-	22.20	9.00	63	13'-2"	1	41.60	42.30	14.00-X-24 14.9-X-28
22	130-170-32	432	330	-	-	27.00	9.00	50	13'-6"	1	46.90	47.70	16.9-X-28
23	130-180-30	457	330	-	-	26.00	7.20	63	13'-8"	1	44.50	45.40	16.9-X-28
													13.00-X-24
24	130-180-32	457	330	-	-	27.20	9.20	63	14.0	1	50.20	51.10	14.00-X-24
\vdash													14.00-X-24 13.00-X-24
25	140-180-32	475	356	-	-	25.40	7.80	60	14.0	1	49.50	50.50	14.00-X-24
													14.00-X-24
	440 400 00	475	250			20.00	7.00		440		55.50	50.50	13.00-X-24
26	140-180-36	475	356	₩	-	28.60	7.80	60	14.0	1	55.50	56.50	14.00-X-24 14.00-X-24
	FILLING TREAD (FT) & UNDER TREAD STRIP (UTS)										14.00-2-24		
<u> </u>										***************************************			
SL. NO.	SIZE Item		m	Base Width (mm)			Tread Thickness (mm)		Wing Thickness (mm)		Wing Width (mm)	Roll Weight	
	Toler	ance	ce		±2 mm			+0.3 mm		mm	+2 mm		
1	FT 23-6	Filling Tread			58			4.80				32 ± 2 Kgs	
2	FT 25-8	Filling Tread		260 (4 Strips 65 mm wide)			6.40				-	32 ± 2 Kgs	
3	FT 30-8	Filling Tread		375 (5 Strips 75 mm wide)			6.40				50 ± 2 Kgs		
4	FT 30-44-10	Filling Tread		223 (2 Strips 76 mm wide)			8.00 4.				32 ± 2 Kgs		
5	FT 30-44-12			223 (2 Strips 76 mm wide)			9.50 4.0		- 12 (A)			2 Kgs	
6	UTS 2mm Under Tread Strip		220			3.00 -				2 Kgs			
7	UTS 3mm Under Tread Strip		220			2.00		3	- 		2 Kgs		
										_			