

To **All Our Esteemed Customers** Wishes a Very Happy & Prosperous New Year 2016

We wish all our esteemed Customers that New Year 2016 will bring enhanced business opportunities with better financial results. We thank all our customers for their continuous support being extended to us which has helped us to improve our performance over the previous year and achieve growth. We assure all our customers our co-operation and continuous support with a commitment to provide best quality materials and complete technical support for mutual benefit and growth in business.

We have introduced the following New Sizes and New Patterns for the benefit of Domestic and International Customers. We are also happy to inform that we are able to get repeat orders from all our International Customers.




● VAMSHI RADIAL RIB (VRR)

Traction Characteristics:

Free Rolling, All Wheel, Excellent Performance

Code	Tread Width (mm)	Tread Thickness (mm)	Non Skid Depth (mm)	Length per Tread (mm)	Under Tread Thickness (mm)	No. of Treads per Roll	Approx Weight per Tread (kg.)	Approx Weight per Package (kg.)	Applications Tyre Sizes Used on
VRR-210	210 mm	17.00 mm	13.50 mm	3300 mm (130")	3.50 mm	3	11.50	34.50	Radial Only 10.00 R 20 & 11 R 22.5
VRR-210 SL	210 mm	17.00 mm	13.50 mm	3225 mm (127")	3.50 mm	3	11.25	33.75	Radial Only 10.00 R 20 & 11 R 22.5



● TURNPIKE (TP)

Traction Characteristics:

Free Rolling, All Wheel, High Performance

TP-127 SL	127 mm	15.10 mm	12.30 mm	3400 mm (134")	2.80 mm	6	6.15	36.90	Bias & Radial 4.50 x 12
-----------	--------	----------	----------	----------------	---------	---	------	-------	----------------------------



● LUG EXCEL (LEX)

Traction Characteristics:

Free Rolling, Rear Axle, Good Traction, Good Performance

LEX-208	208 mm	17.80 mm	14.20 mm	3225 mm (127")	3.60 mm	3	10.90	32.70	Bias Only 10.00 x 20
LEX-208 XL	208 mm	17.80 mm	14.20 mm	3250 mm (128")	3.60 mm	3	11.00	33.00	Bias Only 10.00 x 20
LEX-210 SH	210 mm	20.90 mm	17.50 mm	3250 mm (128")	3.40 mm	2	14.25	28.50	Bias Only 10.00 x 20



● SUPER RIB (SR)

Traction Characteristics:

Free Rolling, All Wheel, Good Traction, High Performance



Code	Tread Width (mm)	Tread Thickness (mm)	Non Skid Depth (mm)	Length per Tread (mm)	Under Tread Thickness	No. of Treads per Roll	Approx Weight per Tread (kg.)	Approx Weight per Package	Applications Tyre Sizes Used on
SR-210 D	210 mm	20.10 mm	16.50 mm	3250 mm (128")	3.60 mm	2	13.60	27.20	Bias & Radial 10.00 x 20 & 10.00 R 20

● ULTRA GRIP RADIAL (UGR)

Traction Characteristics:

Rear Axle, Good Traction, High Performance



UGR-250 D	250 mm	25.60 mm	22.10 mm	3225 mm (127")	3.50 mm	2	19.15	38.30	Radial Only 295 / 70 R 22.5, 295 / 80 R 22.5, 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5
UGR-250 D (SL)	250 mm	25.60 mm	22.10 mm	3100 mm (122")	3.50 mm	2	18.45	36.90	Radial Only 295 / 70 R 22.5, 295 / 80 R 22.5, 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5
UGR-250 D (XL)	250 mm	25.60 mm	22.10 mm	3300 mm (130")	3.50 mm	2	19.60	39.20	Radial Only 295 / 70 R 22.5, 295 / 80 R 22.5, 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5
UGR-250 D (XXL)	250 mm	25.60 mm	22.10 mm	3400 mm (134")	3.50 mm	2	20.20	40.40	Radial Only 295 / 70 R 22.5, 295 / 80 R 22.5, 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5
UGR-250 D (XXXL)	250 mm	25.60 mm	22.10 mm	3750 mm (148")	3.50 mm	2	22.30	44.60	Radial Only 295 / 70 R 22.5, 295 / 80 R 22.5, 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5

● VAMSHI DIRECTIONAL RADIAL (VDR)

Traction Characteristics:

Rear Axle, Good Traction, High Performance



VDR - 270D	270 mm	25.70 mm	22.10 mm	3300 mm (130")	3.60 mm	2	21.80	43.60	Radial Only 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5, 315 / 60 R 22.5
VDR - 270D (SL)	270 mm	25.70 mm	22.10 mm	3125 mm (123")	3.60 mm (123")	2	20.65	41.30	Radial Only 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5, 315 / 60 R 22.5
VDR-270 D (SSL)	270 mm	25.70 mm	22.10 mm	2970 mm (117")	3.60 mm (117")	2	19.65	39.30	Radial Only 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5, 315 / 60 R 22.5
VDR - 270D (XL)	270 mm	25.70 mm	22.10 mm	3400 mm (134")	3.60 mm (134")	2	22.50	45.00	Radial Only 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5, 315 / 60 R 22.5
VDR-270D (XXL)	270 mm	25.70 mm	22.10 mm	3750 mm (148")	3.60 mm (148")	2	24.80	49.60	Radial Only 305 / 70 R 22.5, 315 / 70 R 22.5, 315 / 80 R 22.5, 315 / 60 R 22.5

Hope you liked this NEWSLETTER. We solicit your feed back for improvisation.

Your sincerely,

R. SURENDRA REDDY
Managing Director

**AN ISO 9001-2008
CERTIFIED COMPANY**